

3-Roll Bending Machine



ProStar™ PRSKRMS Forming Roll



ASYMMETRICAL 3-ROLL BENDING MACHINE WITH ONE SIDE PREBEND

FEATURES & APPLICATIONS

- Hardened rollers, suitable even for stainless steel rolling
- Taper-bending fixture
- Motorized rear roller adjustment
- Machine constructed of steel
- High-quality steel rollers
- Rollers are centrally powered by planetary gears
- Top roller swings out
- Self-braking main motor
- Separate control panel
- Meets CE requirements

PRSKRMS157 shown with optional motorized bottom roller adjustment, extended rollers, and profile rollers.

Available Options

- Motor-driven bottom roller adjustment
- Extended roller ends for profile roller mounting
- Profile roller set
- Digital display

SPECIFICATIONS	ROLL LENGTH	PREBEND	SHEET THICKNESS	ROLL DIAMETER	MIN BENDING (Ø)	MOTOR	DIMENSIONS (L/H/W)	WEIGHT
PRSKRMS 15/7	63 in.	.28 in.	.31 in.	6.75 in.	10 in.	5.25 hp	124 in. × 33 in. × 45 in.	4,200 lbs.
PRSKRMS 20/5	83 in.	.20 in.	.24 in.	6.75 in.	10 in.	5.25 hp	144 in. × 33 in. × 45 in.	5,060 lbs.
PRSKRMS 20/6	83 in.	.24 in.	.28 in.	7.5 in.	11.25 in.	5.25 hp	154 in. × 37 in. × 48 in.	7,920 lbs.
PRSKRMS 25/4	102 in.	.16 in.	.20 in.	6.75 in.	10 in.	5.25 hp	164 in. × 33 in. × 45 in.	6,050 lbs.
PRSKRMS 25/5	102 in.	.20 in.	.24 in.	7.5 in.	11.25 in.	5.25 hp	174 in. × 37 in. × 48 in.	9,300 lbs.
PRSKRMS 30/3	122 in.	.12 in.	.16 in.	6.75 in.	10 in.	5.25 hp	183 in. × 33 in. × 45 in.	7,100 lbs.
PRSKRMS 30/4	122 in.	.16 in.	.20 in.	7.5 in.	11.25 in.	5.25 hp	183 in. × 37 in. × 48 in.	10,200 lbs.

Specifications subject to change without notice. Consult your Praxair representative when ordering.