

Stationary Filter Units



ProStar™ MonoGo^{plus}™

Stationary Filter Unit With Flexible Extraction Arm

The MonoGo^{plus} is a stationary welding fume filter system with an integrated fan, filtration and KUA metal tube extraction arm. It contains a two-stage disposable filter system consisting of a pre-filter and deep pleated main filter. It is designed for light to medium duty GTAW/GMAW/SMAW/FCAW applications.



SPECIFICATIONS		SPECIFICATIONS	
PART NUMBER	PRS PLYMGP	AM DIAMETER	6 in. (7 ft. / 10 ft. / 13 ft. L)
FAN AIRFLOW RATE	600 CFM	*ESTIMATED USAGE RATES	SMAW-200 lbs. / GMAW-400 lbs.
MOTOR	1.5 HP / 1.1 kW IEC	ELECTRICAL CONTROLS	Remote on/off switch
BLOWER	Radial at 3,400 RPM		Thermal overload protection
POWER REQUIREMENTS	115 V / 1 Ph / 60 Hz at 14 Amps	SPARK ARRESTANCE	Metal baffle plate
PRE-FILTER	10.8 sq. ft. / polyester	SOUND LEVEL	67 dB(A)
MAIN CARTRIDGE FILTER	280 sq. ft. / E12 HEPA glass fiber	UNIT SIZE	24 in. × 39 in. × 30 in.
FILTER STATUS INDICATOR	Filter full led indicator	UNIT WEIGHT	175 lbs. without arm
FILTER CLEANING	N/A	APPLICATIONS	GTAW / GMAW / SMAW / FCAW

*Estimated usage rates are dependent on ambient air conditions, base metal type and condition, and welding process. Specifications subject to change without notice. Consult your Praxair representative when ordering.

ProStar DualGo^{plus}

Stationary Filter Unit With Dual Flexible Extraction Arm

The DualGo^{plus} is a stationary welding fume filter system with an integrated fan, filtration and two KUA metal tube extraction arms. It contains a two-stage disposable filter system consisting of a pre-filter and deep pleated main filter. It is designed for light to medium duty GTAW/GMAW/SMAW/FCAW applications.



SPECIFICATIONS		SPECIFICATIONS	
PART NUMBER	PRS PLYDGP	AM DIAMETER	6 in. (7 ft. / 10 ft. / 13 ft. L)
FAN AIRFLOW RATE	600 CFM	*ESTIMATED USAGE RATES	SMAW-400 lbs. / GMAW-800 lbs.
MOTOR	1.5 HP / 1.1 kW NEMA IE3	ELECTRICAL CONTROLS	Remote on/off switch
BLOWER	Radial at 3,400 RPM		Thermal overload protection
POWER REQUIREMENTS	115 V / 1 Ph / 60 Hz at 14 Amps	SPARK ARRESTANCE	Metal baffle plate
PRE-FILTER	10.8 sq. ft. / polyester	SOUND LEVEL	79 dB(A) without optional silencer
MAIN CARTRIDGE FILTER	280 sq. ft. / E12 HEPA glass fiber	UNIT SIZE	25 in. × 40 in. × 30 in.
FILTER STATUS INDICATOR	Filter full led indicator	UNIT WEIGHT	289 lbs. without arm
FILTER CLEANING	N/A	APPLICATIONS	GTAW / GMAW / SMAW / FCAW

*Estimated usage rates are dependent on ambient air conditions, base metal type and condition, and welding process. Specifications subject to change without notice. Consult your Praxair representative when ordering.